

COMBY GIGANT



CC40G



Caratteristiche generali

- una sezione dischi ondulati diametro 630 mm, spessore 6 mm
- due file di molle Chisel bilama 55x20+25

A richiesta è possibile applicare un rullo a gabbia diametro 400 mm



Main characteristics:

- a disc section, with wavy discs, diameter 630 mm, thickness 6 mm
- two rows of Chiles spring, two leaves 55x20+2







It is possible to mount a cage roller, diameter 400 mm, on request.



Генеральная характеристика:

- одна секция волнистых дисков диаметром 630мм, толщина 6мм;
- два ряда пружинных стоек 55x20+25

На заказ: решетчатый каток диаметром 400 мм.

Mod. Модель		 mm	 Kg КГ	 N°	 N°	 HP Л.С.
CC40G		2500	1700	15	16	160-190*
CC50G		2500	2600	19	20	250-300*

*La potenza richiesta può variare in base al tipo di terreno (sabbioso, argilloso, molto secco, umido) - The requested power can change according to the type of soil (sandy, clayey, dry, wet) - Потребляемая мощность может меняться в зависимости от типа грунта (песчаный, глинистый, очень сухой, влажный).



Bagnoli di Sopra (Padova) Italy
 Loc. S. Siro - Via F.lli Bandiera, 12
 Tel. +39 049 5344011 - Fax +39 049 5344900
 info@dantemacchine.it
dantemacchine.it

